

# Tetra

## Personal Multigas Monitor

Oxygen, Toxic & Flammable Gases

CO<sub>2</sub>  
H<sub>2</sub>S  
Cl<sub>2</sub>  
NH<sub>3</sub>  
O<sub>3</sub>  
CO  
O<sub>2</sub>  
CH<sub>4</sub>  
SO<sub>2</sub>  
CO<sub>2</sub>  
H<sub>2</sub>S



## TETRA

Tetra is a single button, reliable and robust multigas monitor with optional internal pump. Featuring intelligent sensor modules, shockproof construction and self checking software, Tetra is simple to use and assures reliable gas detection in the toughest of environments.

### Simple

- Single button operation
- Easy to read backlit display for gas readings and diagnostics
- Clear calibration due warning
- Rechargeable Li-ion battery gives 12 hours of continuous operation

### Alarms

- Loud 94dBA audible alarm
- Ultra bright dual red/blue visual alarm
- Vibrating alarm

### Robust

- Rugged plastic housing with flexible internal assembly to resist shock and vibration
- Durable over moulded rubber for added protection
- Water and dust resistant to IP65

### Flexible

- Optional built-in pump
- Rechargeable and alkaline battery versions available
- Compatible with Crowcon Portables PC Software
- Fully interchangeable intelligent sensor modules

# TETRA

Tetra is a personal multigas monitor with an optional built-in pump designed to reliably detect gas in the toughest of environments.

## Gases and Ranges

Required ranges and alarms may vary by country and application and can be configured as required. Each gas channel can have two instantaneous alarm levels set. Toxic channels also have Time Weighted Average (TWA) alarms.

Flammable gas calibration is available for methane, propane, butane, pentane, hydrogen and ethylene as standard.

Tetra is also available in a safe area CO<sub>2</sub> version offering 0-5% carbon dioxide measurement.

### Typical ranges and alarms

Gas	Range	Standard Alarm (UK)
Flammable	0-100% LEL	20% LEL
Oxygen	0-25%	19/23%
Hydrogen sulphide	0-100ppm	5ppm
Carbon monoxide	0-500ppm	30ppm
Sulphur dioxide	0-20ppm	1ppm
Chlorine	0-20ppm	0.5ppm
Nitrogen dioxide	0-20ppm	1ppm
Ammonia	0-100ppm	25ppm
Ozone*	0-1ppm	0.1ppm
Hydrogen	0-1000ppm	N/A
Hydrogen cyanide	0-25ppm	5ppm
Hydrogen fluoride	0-10ppm	1ppm
Phosphine	0-5ppm	0.2ppm
Fluorine	0-1ppm	0.1ppm
Phosgene	0-1ppm	0.1ppm
Carbon dioxide	0-5%	0.5%

## Gas Test Kit

\* unpumped only

The Gas Test Kit provides a simple and convenient means of carrying out either a pre-use (bump) test or a simultaneous four gas calibration (flammable, oxygen, hydrogen sulphide and carbon monoxide only).

## PC Interface and Calibration

Tetra can be routinely calibrated either manually or by using Crowcon Portables PC software or Checkbox IMH packages, providing the user with full configuration control, calibration and access to data and event logs files. An IR link is available using a RS232/USB connection from the PC.

## Charging Options

The Tetra can be supplied with:

- Plug in charging power supplies with UK, EU or US plug or in-line 110V/230V supply
- 10-way multicharger with 90-260V in-line power supply with either UK, EU or US mains lead
- Vehicle lighter socket charger for in-vehicle charging



A HALMA COMPANY

**UK:** 2 Blacklands Way, Abingdon Business Park, Abingdon, OXON, OX14 1DY  
+44 (0) 1235 557700 [sales@crowcon.com](mailto:sales@crowcon.com)

**US:** 21 Kenton Lands Road, Erlanger, Kentucky 41018-1845  
+1 859 957 1039 [salesusa@crowcon.com](mailto:salesusa@crowcon.com)

**NL:** Vlamboem 129, 3068JG, Rotterdam  
+31 10 421 1232 [eu@crowcon.com](mailto:eu@crowcon.com)

**SG:** Block 194 Pandan Loop, #06-20 Pantech Industrial Complex, Singapore, 128383  
+65 6745 2936 [sales@crowcon.com.sg](mailto:sales@crowcon.com.sg)

[www.crowcon.com](http://www.crowcon.com)

PO1017 GB Issue 10 May 2010

### Specification:

<b>Weight</b>	498g (1.1lb)
<b>Dimensions</b>	Rechargeable 122 x 128 x 57mm (4.75 x 5 x 2.25 inches) Non-rechargeable 134 x 128 x 57mm (5.25 x 5 x 2.25 inches)
<b>Typical Response Times (T<sub>90</sub>)</b>	Flammable 20 s, Toxic gas 20 s, Oxygen 10 s
<b>Audible Alarms</b>	94dB Multiple alarm sounds allow selection of distinctive tones for different alarm levels
<b>Visible Alarms</b>	Dual colour red/blue flashing LED in gas hazard
<b>Vibrating Alarm</b>	Internal vibrating alarm
<b>Display</b>	128 x 64 graphic LCD with backlight, giving simultaneous display for all gas channels. Graphic symbols for battery (with proportional indication of remaining operation time), pump operation, healthy operation or fault warning. Start up indication when calibration is due within 30 days, calibration overdue, or service required.
<b>Display Mode</b>	Normal display for real time gas concentration levels. Display recall for the Peak readings and TWA.
<b>Datalogging</b>	Timed datalogging: 50 hours at 1-minute data rate Event logging >1500 events
<b>Battery Types</b>	Rechargeable Li-ion battery Non rechargeable pack 3xAA Alkaline cells
<b>Operating Time</b>	Rechargeable - 12 hour minimum based on pumped four gas unit with flammable sensor
<b>Sampling</b>	Hand aspirator or internal electric sampling pump
<b>Operating Temperature Range</b>	-20°C to +55°C (-4°F to +131°F) Toxic and oxygen sensors are not rated for continuous operation at high temperatures. Consult Crowcon if operating temperature are likely to exceed 40°C (104°F) for extended periods.
<b>Humidity</b>	20-90% RH
<b>Ingress Protection</b>	IP65
<b>Approval Codes</b>	
<i>Europe</i>	ATEX II 2G Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ 55°C) BASEEFA 03ATEX0193
<i>International</i>	IECEX Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ 55°C) BAS04.0024
<i>North America</i>	CSA UL/cUL Class I Division I Groups A, B, C, D
<b>Safety Standards</b>	
<i>Europe</i>	EN60079-0, EN60079-11, EN60079-1, 94/9/EC
<i>North America</i>	UL913, CSA22.2, 152
<b>Operation Standards</b>	EN50270, EN50271, IEC61508, EN61779, EN45544

**Calibrations** Tetra can be routinely calibrated manually using the menu, using Crowcon Portables PC software or automatically using Checkbox IMH.

**Accessories** Tetra is supplied with an integral belt/pocket clip. Pumped units are supplied with a sampling kit (flowplate and 2m (6ft) tubing).

**Optional Accessories** Universal harness plate, shoulder strap, chest harness, carry case, aspirator assembly (flow plate bulb and 2m/6ft tubing), fixed and telescopic sample probes and an in-line water trap.

Crowcon reserves the right to change the design or specification of the product without notice.

Area reserved for distributor stamp

**CROWCON**  
Gas Detection You Can Trust